

Develop No.1 automatic stirrup bending machine

The equipment adopts PLC controller, can process all kinds of stirrup, it can automatically complete straighten, size, bend and cut. The maximum diameter can be bent is 8 mm.

It can process any 2D shapes, widely used in construction site and processing plants .In addition, the device are more perfect after constantly update, can meet all needs from customers



| AUTOMAITC WIRE FEEDING SYSTEM (PLC)/HYDRAULIC CUTTING | | |
|---|------------------------------------|-----------|
| SINGLE WIRE BENDING (MM) | 4-8 ROUND BAR | 4-8 REBAR |
| DOUBLE WIRE BENDING (MM) | 4-6 ROUND BAR | |
| MAX BENDING ANGLE (°) | 180 | |
| MAX TRACTION SPEED(M/MIN) | 60 | |
| MAX BENDING SPEED (°/S) | 800 | |
| ANGLE PRECISION(°) | ±1 | |
| CUT LENGTH PRECISION(MM) | ±1 | |
| AVERAGE POWER(KW/H) | 4.5 | |
| TOTAL POWER(KW) | 15.5 | |
| DIMENSION(MM)(L*W*H) | 2600*880*1700 | |
| WEIGHT(KG) | 1150 | |
| PRODUCTIVITY(DOUBLE WIRE) (PCS/H) | 1600(FOR EXAMPLE 200*200MM SQUARE) | |
| CERTIFICATION | CE/ISO9001:2008 | |